

Hybrid Formula

A one part, high quality, high modulus sealing and bonding material based on advanced hybrid polymer technology. A totally neutral "hybrid" sealant for use in areas requiring a tough elastic rubber joint or as an adhesive with superior bonding strength.

Uses:

Prestige Hybrid Formula can be used for filling and sealing of connecting joints, cracks, holes, etc in the building sector. Bonding metal to metal (can absorb vibration). As a universal waterproof construction adhesive for bonding concrete, mirrors, gypsum board, polycarbonates, polystyrene, PVC, many plastics, ceramics, copper, lead, zinc, aluminium, stainless steel, wood and glass.

Preparation:

Ensure all surfaces are clean and free from grease, oil or any other contaminants that may hinder adhesion.

Applications

- ✓ Apply using a standard sealant gun.
- ✓ Apply in beads or strips (Adhesive)
- ✓ Apply in a continuous bead along the aperture (Sealant)
- ✓ Screw on the nozzle supplied and cut at an angle approximately 45o
- ✓ Remove any excess material and clean tools immediately with white spirit.

This product may cause staining on marble and other stone surfaces. This can be avoided by using a sealer prior to application. Do not use for bedding in double glazed units, for this application we would recommend our LN7 silicone.



Curing in 24 Hours	2.5mm
Shrinkage	NII
Skinning Time	Approx 10 minutes
Hardness Shore A	45+/-4
Temperature Resistance	-30oC to +95oC
Application Temperature	+5oC to +40oC
Storage Temperature	+5oC to +25oC

Storage:

In original, unopened cartridge, stored in a cool, dry place at a temperature between +5oC and +30oC

Shelf Life:

Clear - use within 9 months, colours - use within 12 months

Limitations:

Please note this product is not recommended for use with expansion joints or for installations where the joints are continually immersed in water.

Disposal of Containers:

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

HEALTH & SAFETY:

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

NOTE: This information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.