

Multi-Purpose Silicone

A multi-purpose, low modulus silicone rubber sealant with fungicide, suitable for most sealing jobs around the home.

Uses:

Prestige everyday Sealant is suitable for sealing and waterproofing in areas of high humidity. It has excellent adhesion to glass, glazed surfaces, ceramic tiles, many plastics and most paints. It is ideal for the following applications - kitchen work tops, bathrooms, showers, utility rooms and general DIY applications.

- ✓ Car
- ✓ Caravan
- ✓ Boat
- ✓ House

Preparation:

Ensure all surfaces are clean, dry and free from grease or any contaminants that may hinder adhesion. For best results on movement joints, Expanding Foam is recommended as a backing material, or a suitable backing tape or rod. All cements, concretes and bare metal surfaces should be primed prior to the application of the silicone. Timber should be primed and painted.

Application:

Apply using a standard sealant gun with the nozzle cut at an angle of 45°, and to an opening slightly larger than the joint to be sealed. Tool using a stick or plastic spatula wetted with soapy water. Do not apply to wet surfaces, although wetting immediately afterwards will not have any adverse effects. Tools can be cleaned in white spirit prior to curing taking place.

Maintenance:

Resistant to all common household cleaning chemicals. In showers and bathrooms best results are obtained with a weekly clean to prevent organic build up. Stains can be removed with commercial bleach.



Tooling Time	5-10 minutes
Tack Free Time	Less than 30 minutes
Cure Time	1-2mm per day
Application Temperature	+5 to + 30°C
Service Temperature	-40 to + 100°C
Movement Accomodation	20%
Adhesion	Good to glass, painted surfaces & common building materials
UV Resistance	Excellent
Ozone Resistance	Excellent

Storage:

Store in cool, dry conditions.

Shelf Life:

12 months in original unopened cartridges.

Colours:

Prestige Everyday Sealant comes in 4 colours: white, black, translucent and brown.

Container Size:

EU3 plastic cartridge.

Cleaning of Tools:

Use white spirit.

Disposal of Containers:

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Limitations:

Where bare ferrous metals, brass copper, lead, aluminium or zinc cannot be primed, use a LMN Silicone Sealant. Do not use on surfaces where water can penetrate through porous materials to bond interface without first carrying out remedial work. Not suitable for fixing of mirrors or sealing natural marble.

**Facade sealant for exterior and interior use.
Sanitary sealant.**

HEALTH & SAFETY:

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

NOTE: This information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Reaction to Fire	E
Release of Chemicals	None
Resistance to Flow	< 3mm
Loss of Volume	< 30%
Tensile properties after water immersion	NF
Durability	Pass
Microbiological Growth	S1